

OVERVIEW



This is chassis-mounting potentiometer transmitter with dual-output that detects the variation of resistance with potentiometer and converts it into any desired standard process signal.

- ▽ Anti-humid coatings on PCB are standard for improved environmental protection.
- ▽ Multiple installations on chassis provide ease of maintenance and high-density population.
- ▽ Self pop-up screws on chassis provide ease of wiring.
- ▽ Fuse on DC power line is installed standard.

ORDERING INFORMATION

Ordering Code	Standard Price
MS3910 8	OPEN

SPECIFICATIONS

POWER SECTION

Power Requirement	24V DC ±10%
Power Sensitivity	±0.1% of span max. @10% variance
Power Line Fuse	300mA fuse is installed, (standard)
Power Consumption	55mA max.

INPUT SECTION

Input Range	Between 0~100 Ω to 0~10K Ω.
Measurement Voltage	Approx. 0.5V
Allowable Input Lead-Wire Resistance	10%F.S. /wire max. (Resistance of each line shall be the same.)

OUTPUT SECTION

Output Signal (Specify at ① when ordering)	Out-1/Out-2 Code ■ 1~5V DC/1~5V DC V1 ■ 0~5V DC/0~5V DC V5 ■ 0~10V DC/0~10V DC V6 ■ 1~5V DC/4~20mA DC C1 Combinations of two output signals are limited to the above.
Maximum Output Load	Voltage output: 2mA max. Current output: 300 Ω max.
Zero Adjustment	Approx. 0~30% of span (Adjustable by front-access trimmer)
Span Adjustment	Approx. 70~100% of span (Adjustable by front-access trimmer)

PERFORMANCE

Accuracy Rating	±0.2%/F.S (25°C ±5°C)
Temperature Effect	±0.2% of span @10°C variance
Response Time	170msec max. (0→90% @100% step input)
CMRR	100dB min. (500V AC, 50/60Hz)
Isolation	Across Input, Out-1, Out-2 and Power input mutually
Insulation Resistance	100M Ω min. (@500V DC) Across Input, Out-1, Out-2 and Power input mutually
Dielectric Strength	Across Input and other ports: 1500V AC for 1 minute Across Out-1, Out-2, Power input mutually: 500V AC for 1 minute
Surge Withstand Capability	Tested for ANSI/IEEE C37.90.1-1989
Operating Environment	Ambient temperature: 0~55°C Humidity: 90% max. (Non-condensation)
Storage Temperature	-10~60°C

PHYSICAL

Installation	Installed on mounting base (RC3900-□□Al)
External Connection	Wired to mounting base (RC3900-□□Al)
Dimension	W19.5×H53×D84mm
Weight	Approx. 70g


MATERIAL

Housing	ABS Resin (UL94V-0)
PC Board	Glass Fabric, Epoxy Resin (CEM-3)
Anti-humidity Coating	HumiSeal 1A27NS (Polyurethane)

ADDITIONAL

Other Options	Please consult our sales representatives for the availability of the following options before ordering: (Items) (How to specify) Change response frequency $F_c = \square\square\square\text{Hz}$ (Up to 200Hz) Change response time ... $T_c = \square\square\square\text{sec}$ (Up to 2msec @90%)
---------------	--

TERMINAL ASSIGNMENT



端子	信号号	端子	信号号
①	A POT	⑦	+ OUTPUT 1
②	B POT	⑧	- OUTPUT 1
③	N. C.	⑨	+ OUTPUT 2
④	N. C.	⑩	- OUTPUT 2
⑤	C POT	①	+ POWER DC24V
⑥	N. C.	②	- POWER DC24V
		③	N. C.
		④	N. C.
		⑤	F. G.
		⑥	N. C.

BLOCK DIAGRAM

