

**OVERVIEW**



This is chassis-mounting PT transmitter with dual-output that converts AC voltage signal from PT into any desired standard process signal.

- ▽ RMS operation for measuring distorted waveform.
- ▽ Anti-humid coatings on PCB are standard for improved environmental protection.
- ▽ Multiple installations on chassis provide ease of maintenance and high-density population.
- ▽ Self pop-up screws on chassis provide ease of wiring.
- ▽ Fuse on DC power line is installed standard.

**ORDERING INFORMATION**

Ordering Code	Standard Price
MS3921 1 8	OPEN

**SPECIFICATIONS**

**POWER SECTION**

Power Requirement	24V DC ±10%
Power Sensitivity	±0.1% of span max. @10% variance
Power Line Fuse	300mA fuse is installed, (standard)
Power Consumption	55mA max.

**INPUT SECTION**

Input Signal (Specify at ①when ordering)	<ul style="list-style-type: none"> <li>■ 0~100V AC 50/60Hz ..... N1</li> <li>■ 0~110V AC 50/60Hz ..... N2</li> <li>■ 0~300V AC 50/60Hz ..... N3</li> <li>■ Other AC voltage signal up to 300V (50/60Hz) .... NX (□~□) Specify input range in parentheses.</li> </ul>
Input Resistance	1MΩ min. (1MΩ minimum without power)

Allowable Input Voltage	Continuous: 120% rated input Instantaneous: 1.5×rated input (5sec)
Crest Fact	3 max.

**OUTPUT SECTION**

Output Signal (Specify at ②when ordering)	Out-1/Out-2 ..... Code ■ 1~5V DC/1~5V DC ..... V1 ■ 0~5V DC/0~5V DC ..... V5 ■ 0~10V DC/0~10V DC ..... V6 ■ ±5V DC/±5V DC ..... W5 ■ ±10V DC/±10V DC ..... W6 ■ 1~5V DC/4~20mA DC ..... C1 Combinations of two output signals are limited to the above.
Maximum Output Load	Voltage output: 2mA max. Current output: 300Ω max.
Zero Adjustment	Approx. ±2% of span (Adjustable by front-access trimmer)
Span Adjustment	Approx. ±2% of span (Adjustable by front-access trimmer)

**PERFORMANCE**

Accuracy Rating	±0.25%/F.S. (On condition of 10% input as minimum) (25°C ±5°C)
Temperature Effect	±0.2% of span @10°C variance
Response Time	0.4sec max. (0→90% @100% step input)
CMRR	100dB min. (500V AC, 50/60Hz)
Isolation	Across Input, Out-1, Out-2 and Power input mutually
Insulation Resistance	100MΩ min. (@500V DC) Across Input, Out-1, Out-2 and Power input mutually
Dielectric Strength	Across Input and other ports: 1500V AC for 1 minute Across Out-1, Out-2, Power input mutually: 500V AC for 1 minute
Surge Withstand Capability	Tested for ANSI/IEEE C37.90.1-1989
Operating Environment	Ambient temperature: 0~55°C Humidity: 90% max. (Non-condensation)
Storage Temperature	-10~60°C

**PHYSICAL**

Installation	Installed on mounting base (RC3900-□□AI)
External Connection	Wired to mounting base (RC3900-□□AI)
Dimension	W19.5×H53×D84mm
Weight	Approx. 70g


**MATERIAL**

Housing	ABS Resin (UL94V-0)
PC Board	Glass Fabric, Epoxy Resin (CEM-3)
Anti-humidity Coating	HumiSeal 1A27NS (Polyurethane)

**ADDITIONAL**

Other Options	Please consult our sales representatives for the availability of the following options before ordering: 〈Items〉 ..... 〈How to specify〉 ■ Change response time ... $T_c = \square\square\square$ sec (Up to 80msec @90%)
---------------	--

**TERMINAL ASSIGNMENT**



端子	信号号	端子	信号号
①	N. C.	⑦	+ OUTPUT 1
②	N. C.	⑧	- OUTPUT 1
③	N. C.	⑨	+ OUTPUT 2
④	N. C.	⑩	- OUTPUT 2
⑤	N INPUT	①	+ POWER DC24V
⑥	L INPUT	②	- POWER DC24V
		③	N. C.
		④	N. C.
		⑤	F. G.
		⑥	N. C.

**BLOCK DIAGRAM**

